



Rymax Endurox XLD SAE 10W/40

Safety Data Sheet

according to Regulation (EC) No. 453/2010

MADE IN HOLLAND

Date of issue: 12-02-2014

Revision date: 12-02-2014

Supersedes: 12-02-2014

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Rymax Endurox XLD SAE 10W/40
Product code : lub002036
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : industrial use, professional use, consumer use
Use of the substance/mixture : Lubricant
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Rymax b.v.
Delweg 8
6902 PJ Zevenaar
The Netherlands
info@rymax-lubricants.com
tel: +31 (0) 316-740856

1.4. Emergency telephone number

Emergency number : +31 (0)316 740 856
(Monday to Friday: 8:00 - 17:00)

Country	Organisation/Company	Address	Emergency number
GREECE	Poisons Information Centre Children's Hospital "Aglaia. Kyriakou"	11527Athens	+30 10 779 3777
ICELAND	Iceland Poisons Information Centre Landspítali University Hospital	Fossvogi 108Reykjavik	+354 525 111 +354 543 2222
IRELAND (REPUBLIC OF)	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9Dublin	: +353 1 8379964
ISRAEL	Israel Poisons Information Centre Rambam Medical Centre	PO Box 9602 31096Haifa	+972 4 854 1900
UNITED KINGDOM	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LPNewcastle	0870 600 6266 (UK only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children
EUH phrases : EUH208 - Contains Calcium long chain alkaryl sulfonate, Salts of alkyl hydroxybenzoic acids.
May produce an allergic reaction

Rymax Endurox XLD SAE 10W/40

Safety Data Sheet

according to Regulation (EC) No. 453/2010

2.3. Other hazards

Other hazards not contributing to the classification

: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L)". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based substance with national workplace exposure limit(s) (FI, IT, PT)	(CAS No)72623-87-1 (EC no)276-738-4 (REACH-no)01-2119474889-13	35 - 50	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS No)64742-54-7 (EC no)265-157-1 (EC index no)649-467-00-8	25 - 35	Not classified
Highly refined mineral oil (C15 -C50)		10 - 25	Not classified
Polyolefin polyamine succinimide, polyol		2,5 - 5	R53
Polyolefin polyamine succinimide, borated		1 - 2,5	R53
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	(CAS No)68649-42-3 (EC no)272-028-3 (REACH-no)01-2119657973-23	1 - 2,5	Xi; R41 N; R51/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based substance with national workplace exposure limit(s) (FI, IT, PT)	(CAS No)72623-87-1 (EC no)276-738-4 (REACH-no)01-2119474889-13	35 - 50	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS No)64742-54-7 (EC no)265-157-1 (EC index no)649-467-00-8	25 - 35	Asp. Tox. 1, H304
Highly refined mineral oil (C15 -C50)		10 - 25	Asp. Tox. 1, H304
Polyolefin polyamine succinimide, polyol		2,5 - 5	Aquatic Chronic 4, H413
Polyolefin polyamine succinimide, borated		1 - 2,5	Aquatic Chronic 4, H413
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	(CAS No)68649-42-3 (EC no)272-028-3 (REACH-no)01-2119657973-23	1 - 2,5	Eye Dam. 1, H318 Aquatic Chronic 2, H411

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Seek medical attention if ill effect develops.
First-aid measures after inhalation	: Take victim to fresh air, in a quiet place, in a half laying position and if necessary take medical advice. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.
First-aid measures after ingestion	: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.

Rymax Endurox XLD SAE 10W/40

Safety Data Sheet

according to Regulation (EC) No. 453/2010

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/injuries after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Symptoms/injuries after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/injuries after ingestion	: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
Symptoms/injuries upon intravenous administration	: Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide (CO ₂), dry chemical powder, foam. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustion generates : CO, CO ₂ , PO _x , NO _x , SO _x , H ₂ S. Metallic oxides.
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.

5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.
Other information	: Prevent fire-fighting water from entering environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures	: Consider evacuation.

6.1.2. For emergency responders

Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures	: No specific measures are necessary.

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and material for containment and cleaning up

For containment	: Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

6.4. Reference to other sections

For further information refer to section 13.

Rymax Endurox XLD SAE 10W/40

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
- Precautions for safe handling : Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.
- Hygiene measures : Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep container tightly closed and in well ventilated place.
- Storage conditions : Store in original container.
- Incompatible products : Reacts vigorously with strong oxidizers and acids.
- Maximum storage period : 5 year
- Storage temperature : ≤ 40 °C.
- Prohibitions on mixed storage : Keep away from : oxidizing materials. strong acids.
- Storage area : Store at ambient temperature.
- Special rules on packaging : Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Highly refined mineral oil (C15 -C50)		
EU	IOELV TWA (mg/m ³)	5 mg/m ³

Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based (72623-87-1)		
Finland	HTP-arvo (8h) (mg/m ³)	5 mg/m ³
USA - ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³

Exposure-value for oil mist : 10 mg/m³ (15 min.) or 5 mg/m³ (8 hours).

Rymax Endurox XLD SAE 10W/40

Safety Data Sheet

according to Regulation (EC) No. 453/2010

8.2. Exposure controls

- Appropriate engineering controls : Large quantities: Contain large spillage with sand or earth.
- Personal protective equipment : Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.



- Materials for protective clothing : PVC gloves. Neoprene or nitrile rubber gloves.
- Hand protection : In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).
- Eye protection : Eye protection should only be necessary where liquid could be splashed or sprayed.
- Skin and body protection : No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.
- Respiratory protection : Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.
- Environmental exposure controls : See Heading 12. See Heading 6.
- Consumer exposure controls : PVC gloves. Neoprene or nitrile rubber gloves.
- Other information : Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : liquid
- Appearance : Oily. liquid.
- Colour : Brown.
- Odour : characteristic.
- Odour threshold : no data available
- pH : no data available
- Relative evaporation rate (butylacetate=1) : < 0,1
- Melting point : <= -36 °C.
- Freezing point : no data available
- Boiling point : > 280 °C.
- Flash point : 220 °C.
- Auto-ignition temperature : > 240 °C.
- Decomposition temperature : no data available
- Flammability (solid, gas) : no data available
- Vapour Pressure 20°C : < 0,1 hPa
- Relative vapour density at 20 °C : > 1 (air=1)
- Relative density : no data available
- Density : 0,855 - 0,865 kg/l
- Solubility : insoluble in water.
- Log Pow : > 3
- Viscosity, kinematic @ 20 °C : 150 - 300 cSt
- Viscosity, dynamic : no data available
- Explosive properties : no data available
- Oxidising properties : no data available
- Explosive limits : 0,6 - 7 vol %

9.2. Other information

Rymax Endurox XLD SAE 10W/40

Safety Data Sheet

according to Regulation (EC) No. 453/2010

VOC content : 0 %
Other properties : Gas/vapour heavier than air at 20°C.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. strong acids.

10.6. Hazardous decomposition products

CO, CO₂, PO_x, NO_x, SO_x, H₂S. Metallic oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based (72623-87-1)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 inhalation rat (mg/l)	> 5,53 mg/l/4h (OECD 403 method)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : Not classified

Rymax Endurox XLD SAE 10W/40	
Viscosity, kinematic @ 20 °C	150 - 300 mm ² /s

Other information : Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Ecology - water : This product floats on water and may affect the oxygen-balance in the water.

Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based (72623-87-1)	
LC50 fishes 1	≈ 100 mg/l (OECD 203 method)

12.2. Persistence and degradability

Rymax Endurox XLD SAE 10W/40	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

Rymax Endurox XLD SAE 10W/40	
Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.

Rymax Endurox XLD SAE 10W/40

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based (72623-87-1)

Log Kow	> 6
---------	-----

12.4. Mobility in soil

Rymax Endurox XLD SAE 10W/40

Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.
----------------	--

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information	: Hazardous waste.
Ecology - waste materials	: Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW) code	: 13 02 06* - Synthetic engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (UN)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

Rymax Endurox XLD SAE 10W/40

Safety Data Sheet

according to Regulation (EC) No. 453/2010

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

14.6.1. Overland transport

14.6.2. Transport by sea

14.6.3. Air transport

14.6.4. Inland waterway transport

Not subject to ADN : No

14.6.5. Rail transport

Carriage prohibited (RID) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

Contains no substance on the REACH candidate list

VOC content : 0 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H304	May be fatal if swallowed and enters airways
H318	Causes serious eye damage
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life
R41	Risk of serious damage to eyes
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R53	May cause long-term adverse effects in the aquatic environment
N	Dangerous for the environment
Xi	Irritant

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product