



Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

MADE IN HOLLAND

Date of issue: 20-7-2018 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product code : Lub002098

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Rymax b.v.
Delweg 8
6902 PJ Zevenaar
T +31 (0)316 740840 - F +31 (0)316 740844
info@rymax-lubricants.com - www.rymax-lubricants.com

1.4. Emergency telephone number

Emergency number : +31 (0)316 740840

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-Decene, homopolymer, hydrogenated	(CAS-No.) 68037-01-4 (EC-No.) 500-183-1 (REACH-no) 01-2119486452-34	25 - 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	25 - 50	Asp. Tox. 1, H304

Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.]	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (EC Index-No.) 649-483-00-5 (REACH-no) 01-2119474889-13	1 - 10	Asp. Tox. 1, H304
Decanoic acid, ester with 2-ethyl-2-(hydroxymethyl) -1,3-propanediol octanoate	(CAS-No.) 11138-60-6 (EC-No.) 234-392-1	5 - 10	Not classified
bis(nonylphenyl)amine	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911, 01-2119488911-28	0,1 - 5	Aquatic Chronic 4, H413
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)	(CAS-No.) 2215-35-2 (EC-No.) 218-679-9 (EC Index-No.) 01-2119953275-34 (REACH-no) 01-2119953275-34	0,5 - 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Zinc bis(O-(6-methylheptyl)) bis (O(sec-butyl)) bis dithiophosphate	(CAS-No.) 93819-94-4 (EC-No.) 298-577-9 (REACH-no) 01-2119543726-33	0,1 - 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	(CAS-No.) 125643-61-0 (EC-No.) 406-040-9 (EC Index-No.) 607-530-00-7 (REACH-no) 01-0000015551-76	0,1 - 0,5	Aquatic Chronic 4, H413
PPD		0,1 - 0,5	Not classified
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	(EC-No.) 457-320-2 (REACH-no) 01-0000019337-66	0,01 - 0,5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)	(CAS-No.) 2215-35-2 (EC-No.) 218-679-9 (EC Index-No.) 01-2119953275-34 (REACH-no) 01-2119953275-34	(10 =<C < 100) Eye Dam. 1, H318
Zinc bis(O-(6-methylheptyl)) bis (O(sec-butyl)) bis dithiophosphate	(CAS-No.) 93819-94-4 (EC-No.) 298-577-9 (REACH-no) 01-2119543726-33	(6,25 <C <= 100) Skin Irrit. 2, H315 (10 <C <= 12,5) Eye Irrit. 2, H319 (12,5 <C <= 100) Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

EU	IOELV TWA (mg/m ³)	5 mg/m ³
Belgium	Limit value (mg/m ³)	5 mg/m ³
USA - ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA - ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.] (72623-87-1)

EU	IOELV TWA (mg/m ³)	5 mg/m ³
EU	IOELV STEL (mg/m ³)	10 mg/m ³

bis(nonylphenyl)amine (36878-20-3)

USA - ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA - ACGIH	ACGIH STEL (mg/m ³)	10 fibers/cm ³
USA - ACGIH	ACGIH STEL (ppm)	0 ppm

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

USA - ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA - ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

EU	IOELV TWA (mg/m ³)	5 mg/m ³
EU	IOELV STEL (mg/m ³)	10 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Eye protection:

Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -39 °C
Boiling point	: No data available
Flash point	: > 201 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 855,4 kg/m ³ @15°C
Solubility	: insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: 177,6 mm ² /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

1-Decene, homopolymer, hydrogenated (68037-01-4)	
LD50 oral (rat)	5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	5,2 mg/l/4h

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)	
LD50 oral	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	5,53 mg/l/4h

Decanoic acid, ester with 2-ethyl-2-(hydroxymethyl) -1,3-propanediol octanoate (11138-60-6)	
LD50 oral (rat)	> 2000 mg/kg OECD 401
LD50 dermal (rabbit)	> 2000 mg/kg OECD 402
LC50 inhalation (rat) (mg/l)	5,1 mg/l/4h OECD Test Guideline 403
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5,1 mg/l/4h

bis(nonylphenyl)amine (36878-20-3)	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rat)	> 2000 mg/kg

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
LD50 oral	2230 mg/kg

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)	
LD50 oral (rat)	2600 mg/kg
LD50 dermal (rabbit)	> 3160 mg/kg OECD 402

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LD50 oral (rat)	> 2000 mg/kg OECD 401
LD50 dermal (rat)	> 2000 mg/kg OECD 402

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Molybdenum polysulphide long chain alkyl dithiocarbamate complex	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

1-Decene, homopolymer, hydrogenated (68037-01-4)	
NOAEL (oral, rat, 90 days)	4159,4 mg/kg bodyweight/day
NOAEL (subacute, oral, animal/male, 28 days)	6245 mg/kg bodyweight

Aspiration hazard : Not classified

Motrax R SAE 10W/60	
Viscosity, kinematic	177,6 mm ² /s @40°C

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

EC50 Daphnia 1	10000 mg/l
----------------	------------

Decanoic acid, ester with 2-ethyl-2-(hydroxymethyl) -1,3-propanediol octanoate (11138-60-6)

LC50 fish 1	> 10000 mg/l 96 Hrs (OECD 203)
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea)
ErC50 (algae)	> 100 mg/l (Desmodesmus subspicatus (green algae))

bis(nonylphenyl)amine (36878-20-3)

LC50 fish 1	> 100 mg/l Danio rerio
EC50 Daphnia 1	> 100 mg/l Daphnia magna
EC50 72h algae (1)	> 100 mg/l Desmodesmus subspicatus
NOEC chronic algae	100 mg/l

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

LC50 fish 1	4,5 mg/l
EC50 Daphnia 1	23 mg/l
EC50 72h algae (1)	21 mg/l

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)

LC50 fish 1	4,5 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 Daphnia 1	5,4 mg/l EC50 48h - Daphnia magna [mg/l]
EC50 96h algae (1)	2,1 mg/l Selenastrum capricornutum

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

LC50 fish 1	> 74 mg/l Brachydanio rerio (zebra-fish)
EC50 Daphnia 1	> 100 mg/l Daphnia magna (grote watervlo)
EC50 72h algae (1)	> 3 mg/l Desmodesmus subspicatus (groene algen)

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

LC50 fish 1	94,8 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	50 mg/l Daphnia magna
EC50 72h algae (1)	9,62 mg/l Pseudokirchneriella subcapitata
NOEC (chronic)	100 mg/l
NOEC chronic fish	94,8 mg/l Oncorhynchus mykiss

12.2. Persistence and degradability

1-Decene, homopolymer, hydrogenated (68037-01-4)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

Biodegradation	30 % 28 d OECD 301F
----------------	---------------------

Decanoic acid, ester with 2-ethyl-2-(hydroxymethyl) -1,3-propanediol octanoate (11138-60-6)

Persistence and degradability	Readily biodegradable.
Biodegradation	78,9 % 28 Days (OECD 301B)

bis(nonylphenyl)amine (36878-20-3)

Persistence and degradability	Not biodegradable.
Biodegradation	1 % 28 Days (OECD 301 B)

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

Persistence and degradability	Not readily biodegradable.
Biodegradation	1,5 % 28 DY, OECD TG 301 B

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)

Persistence and degradability	Not readily biodegradable.
Biodegradation	1,5 % OECD-testrichtlijn 301 B

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Persistence and degradability	Not readily biodegradable.
Biodegradation	28D

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

Biodegradation	22,75 % 29 Days
----------------	-----------------

Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

Log Kow > 4

Decanoic acid, ester with 2-ethyl-2-(hydroxymethyl) -1,3-propanediol octanoate (11138-60-6)

Log Pow > 2,7

bis(nonylphenyl)amine (36878-20-3)

Bioconcentration factor (BCF REACH) 1730

Log Pow > 7,6

Bioaccumulative potential Bioaccumulative potential.

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

Log Kow 2,21 @20°C

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)

Log Pow 0,9 @23°C

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Bioconcentration factor (BCF REACH) 260 35 D, Oncorhynchus mykiss (regenboogforel)

Log Pow 9,2

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

BCF fish 1 0,05 mg/l @25°C Cyprinus carpio (Karper)

Bioconcentration factor (BCF REACH) 88

12.4. Mobility in soil

bis(nonylphenyl)amine (36878-20-3)

Ecology - soil Adsorbs into the soil.

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

Ecology - soil Adsorbs into the soil.

Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)

Ecology - soil Adsorbs into the soil.

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Ecology - soil Adsorbs into the soil.

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

Ecology - soil Adsorbs into the soil.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : Not applicable

UN-No. (IMDG) : Not applicable

UN-No. (IATA) : Not applicable

UN-No. (ADN) : Not applicable

UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable

Proper Shipping Name (IMDG) : Not applicable

Proper Shipping Name (IATA) : Not applicable

Proper Shipping Name (ADN) : Not applicable

Proper Shipping Name (RID) : Not applicable

Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 1, low hazard to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Motrax R SAE 10W/60

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Netherlands

- Ministry's list of carcinogens : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Zinc bis(O-(6-methylheptyl)) bis (O(sec-butyl)) bis dithiophosphate) are listed
- Ministry's list of mutagens : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Zinc bis(O-(6-methylheptyl)) bis (O(sec-butyl)) bis dithiophosphate) are listed
- NON-exhaustive list of reproductive toxins - Breastfeeding : None of the components are listed
- NON-exhaustive list of reproductive toxins - Fertility : None of the components are listed
- NON-exhaustive list of reproductive toxins - Evolution : None of the components are listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II) RYMAX

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness