

STYX STOU SS

SEMI SYNTHETIC UNIVERSAL TRACTOR OIL

Description

Styx STOU SS SAE 10W-40 is a multi-grade Super Tractor Oil Universal, elaborated for the application in the engine, transmission, oil immersed "wet" brakes and hydraulic system in tractors, combines, harvesters and off-road equipment with or without turbo-charger engine. Thanks to its universal characteristic, this provide an undoubtable maintenance advantage, preventing mistakes and having a limited stock of products.

Styx STOU SS is formulated with high refined mineral and synthetic base stocks, in combination with a dedicated and unique additive package to fulfil all the requirements of STOU. It can be used all year round, providing a perfect cold start, reduces friction and keep the engine clean. It allows an optimum drain interval. Styx STOU SS also offers a perfect protection against corrosion, oxidation, foam-building and wear, even under extreme high loads in transmissions. An optimum level of detergent and dispersant keeps the oil and the system clean from any impurities.

Styx STOU SS is not applicable in diesel engines equipped with Diesel Particles Filter (DPF).

Benefits

- High level of detergency and dispersancy
- Excellent "Extreme Pressure" properties
- Excellent resistance against oxidation
- Very good protection against wear



Performance levels

Engine Applications

- API CI-4/SF
- ACEA E3

Transmission Applications

- API GL-4/GL-5 Low Speed/High Torque
- John Deere JDM J20C
- MF 1139/1144
- Allison C-4
- ZF TE ML 06A/B/C/07B
- Caterpillar TO-2
- MIL-L-2104D/2105

Multipurpose Applications

- MB 227.1
- Ford M2C 159B/C, 134D
- Ford New Holland 82009202
- John Deere JDM J27



MADE IN HOLLAND

TECHNICAL DATA SHEET

STYX STOU SS

SEMI SYNTHETIC UNIVERSAL TRACTOR OIL

Typical Properties

SAE		10W-40
Code		LUB002065
Density 15 °C	kg/m3	874
Viscosity 40 °C	cSt	94.7
Viscosity 100 °C	cSt	14.5
Viscosity CCS -25 °C	cP	<7000
Viscosity Index		159
Pour Point	°C	-36
Flash Point C.O.C	°C	212
TBN	mg KOH/g	10.7
Operating Temperature	°C	-33/150