

# STYX STOU

## UNIVERSAL TRACTOR OIL

### Description

Styx STOU is a mineral Super Tractor Oil Universal, elaborated for the application in the engine, transmission, oil immersed "wet" brakes and hydraulic system in tractors, combines, harvesters and off-road equipment with or without turbo-charger engine. Thanks to its universal characteristic, this provide an undoubtable maintenance advantage, preventing mistakes and having a limited stock of products.

Styx STOU can be used all year round, providing a perfect cold start, reduces friction and keep the engine clean. It allows an optimum drain interval. Styx STOU also offers a perfect protection against corrosion, oxidation and wear, even under extreme high loads in transmissions. A optimum level of detergent and dispersant keep the oil and the system clean from any impurities.

*Styx STOU is not applicable in diesel engines equipped with Diesel Particles Filter (DPF)*

### Benefits

- High level of detergency and dispersancy
- Excellent "Extreme Pressure" properties
- Excellent resistance against oxidation
- Very good protection against wear



### Performance levels

#### Engine Applications

- API CG-4/SF
- ACEA E3
- MB 227.1

#### Transmission Applications

- API GL-4
- John Deere JDM J20C/D
- Allison C-4
- MF 1135/1139/1143/1144/1145
- ZF TE ML 06A/06B/06C/07B (10W-40)

#### Multipurpose Applications

- Ford M2C 159B/C, 86-B/C, 134D
- John Deere JDM J27
- Case MS 1204/6/7/9
- Eaton M-29505, I-280-S

# STYX STOU

UNIVERSAL TRACTOR OIL

## Typical Properties

SAE		10W-30	15W-30	10W-40	15W-40
Code		LUB002060	LUB002061	LUB002064	LUB002062
Density 15 °C	kg/m <sup>3</sup>	874	875	877	874
Viscosity 40 °C	cSt	67.0	77.5	94	106.4
Viscosity 100 °C	cSt	10.5	10.8	13.5	14.4
Viscosity CCS -20 °C	cP		<7000		<7000
Viscosity CCS -25 °C	cP	<7000		<7000	
Viscosity Index		145	126	145	139
Pour Point	°C	-30	-30	-30	-30
Flash Point C.O.C	°C	>200	>200	>200	>200
TBN	mg KOH/g	10.1	11.0	10.6	11.7
Operating Temperature	°C	-25/150	-25/150	-25/150	-25/150