

# STYX UTTO FS 75W

## FULL SYNTHETIC UNIVERSAL TRACTOR TRANSMISSION OIL



### Description

Styx UTTO FS 75W is especially developed for transmissions and hydraulic, oil-cooled brake and clutch systems, of agricultural, home gardening and industrial tractors. Because of the low pour point, this oil is very suitable for cold climate conditions.

Styx UTTO FS 75W is suitable for modern disc brake materials, specifically wet brakes, and fulfills the requirements of the Volvo WB 102 specifications.

Styx UTTO FS 75W has excellent viscosity properties at low temperatures when compared to regular mineral oil based UTTO products with the same viscosity grade.

*Styx UTTO FS is not an engine oil.*

### Benefits

- Very favourable friction characteristics
- Suitable for use in systems with "wet" brakes
- Prevents from 'stickslip' and the accompanied noise, all year round
- Very good shear stability
- Excellent protection against wear and corrosion.
- Very good anti-foam properties.

### Performance levels

- API GL-4
- Allison C-4
- ZF TE-ML 03E/05F/06K
- Case MS 1207
- Case MS 1206
- CNH MAT 3525
- MF M1145
- MF M1143
- MF M1141
- MF M1135
- Volvo WB 101
- Case MS 1210
- Ford WSS-M2C134-D
- John Deere J20A
- John Deere J20C
- Volvo WB 102
- Caterpillar TO-2

### Typical Properties

SAE	75W		
Code	LUB002076		
Colour	kg/l	0.854	ASTM D 1298
Viscosity 40 °C	cSt	41.2	ASTM D 445
Viscosity 100 °C	cSt	7.8	ASTM D 445
Viscosity Index		161	ASTM D 2270
Pour Point	°C	-42	ASTM D 97
Flash Point C.O.C	°C	211	ASTM D 93