

APOLLO FE-F

FULL SYNTHETIC MID-SAPS ENGINE OIL FOR GASOLINE AND DIESEL ENGINES

Description

Our Apollo FE-F is a full synthetic ultra high performance oil for the use in gasoline and diesel engines in passenger cars, especially designed for the most recent Ford diesel engines. Apollo FE-F fulfills the requirements of Ford WSS-M2C950-A.

Apollo FE-F quickly provides an extremely stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Apollo FE-F offers optimum dispersancy and detergency, keeping the engine clean. Apollo FE-F provides maximum protection against rust and corrosion. The special additives keep all parts free from dirt, sludge and deposits.

It is also recommended for vehicles for which an engine oil meeting ACEA C2 with the viscosity grade 0W-30 is prescribed.



Performance levels

- ACEA C2
- Ford WSS M2C-950A
- STJLR 03.5007

Typical Properties

SAE			0W-30
Colour		Brown	
Density at 20°C	kg/l	0.839	ASTM D 1298
Viscosity, kinematic at 40°C	cSt	47.7	ASTM D 445
Viscosity, kinematic at 100°C	cSt	9.8	ASTM D 445
Viscosity Index		197	ASTM D 2270
Viscosity, dynamic (CCS)	cP	5313	ASTM D 2602
Base number	mg KOH/g	8.0	ASTM D 2896
Flash point	°C	200	ASTM D 93
Pour point	°C	-51	ASTM D 97