

GEVITRO GL-5 LS

LIMITED SLIP GEAR OIL

Description

Gevitro GL-5 LS (Limited Slip) is recommended for passenger cars with "limited slip" differentials. Gevitro GL-5 LS is a high quality, hypoid type gear oil, specifically developed for limited slip differential units fitted to modern, high performance passenger cars and off-road leisure vehicles.

Gevitro GL-5 LS may be used in limited slip differentials of European, Japanese and American built vehicles, and is equally suitable in transmissions, gear axles, steering boxes and universal joints etc. Gevitro GL-5 LS is recommended for high performance passenger cars and sports cars frequently running at high speed and is equally suited in a wide range of applications where an EP-type gear oil is specified.

Benefits

- Optimizes frictional characteristics of the limited slip components
- Effective in reducing transmission noise
- Very good performance at high temperatures
- Gives maximum protection of the gears, bearings and limited-slip components

Typical Properties

SAE		80W-90	85W-140
Code		LUB005011	LUB005019
Density 15 °C	kg/m ³	890	900
Viscosity 40 °C	cSt	142.0	374.0
Viscosity 100 °C	cSt	14.7	26.4
Viscosity Index		103	98
Pour Point	°C	-30	-18
Flash Point C.O.C	°C	210	230
Operating temperature	°C	-25/150	-15/150



Performance levels

- API GL-5
- MIL-L-2105 D
- ZF TE-ML 05C/12C/16E