

## MARLUB 20

### MEDIUM SPEED TRUNK ENGINE OIL

#### Description

MarLub 20 oils are high quality, alkaline dual-purpose engine oils for all medium or high speed marine diesel engines operating on residual type fuels, with a sulphur content up to 2.5% wt. They are blended from high quality paraffin base stocks and proven additives.

MarLub 20 may also be used in both main and auxiliary engines where normally a distillate fuel is being used. MarLub 20 is suited for all marine diesel engines irrespective of make.

*Medium- and high speed diesel engines using fuel with a sulphur content up to 4.5%.*

#### Performance level

- API CF



#### Benefits

- Suitable for engines using residual or distillate fuels
- Superior resistance to oxidation and oil thickening
- Effective neutralization of acidic combustion products
- Excellent detergency to reduce deposit formation
- Long engine and oil service life
- Very good water tolerance and filterability

#### Typical Properties

		SAE 30	SAE 40
Code		LUB005530	LUB005531
Density 15 °C	kg/m <sup>3</sup>	898	905
Viscosity 40 °C	cSt	106	145
Viscosity 100 °C	cSt	11.8	14.5
Viscosity Index		95	95
Pour point	°C	-21	-18
Flash point C.O.C.	°C	200	200
TBN	mg KOH/g	20	20
Operating temperature	°C	-15/150	-10/150