

MARLUB 30

MEDIUM SPEED TRUNK ENGINE OIL

Description

MarLub 30 oils are high quality, alkaline dual-purpose engine oils for all medium or high speed marine diesel engines operating on residual type fuels, with a sulphur content up to 2.5% wt. They are blended from high quality paraffin base stocks and proven additives.

MarLub 30 may also be used in both main and auxiliary engines where normally a distillate fuel is being used. MarLub 30 is suited for all marine diesel engines irrespective of make.

Medium- and high speed diesel engines using fuel with a sulphur content up to 4.5%.

Performance level

- API CF



Benefits

- Suitable for engines using residual or distillate fuels
- Superior resistance to oxidation and oil thickening
- Effective neutralization of acidic combustion products
- Excellent detergency to reduce deposit formation
- Long engine and oil service life
- Very good water tolerance and filterability

Typical Properties

		Marlub 3030	Marlub 3040
Code		LUB005540	LUB005541
Density 15 °C	kg/m3	902	905
Viscosity 40 °C		99.0	134
Viscosity 100 °C	cSt	11.4	14.0
Viscosity Index		100	100
Pour point	°C	-12	-12 m
Flash point C.O.C.	°C	>200	>200
TBN	mg KOH/g	30	30
Operating temperature	°C	-10/150	-10/150