

MOTRAX FO

FORK OIL & SUSPENSION FLUID

Description

Motrax FO is blended from carefully selected paraffinic base oils with a low pour point and a high viscosity index.

Motrax FO is inhibited with very effective additives, ensuring an exceptional hydraulic springing and shock absorbing action. Scuffing and wear are reduced to a minimum, while a smooth movement is guaranteed. Besides, this oil offers good protection against foam-building and corrosion. Seals are not affected by this product.

Motrax FO has a high thermal and oxidation stability and can be applied in a broad temperature range. Due to the stable viscosity index improvers, the viscosity will stay in grade over a very long time.



Typical Properties

		SAE 2,5	SAE 5	SAE 10	SAE 15	SAE 20
Code		LUB004050	LUB004051	LUB004052	LUB004053	LUB004054
Colour		Amber	Red	Red	Red	Red
Density 20 °C	kg/m ³	8232	8636	8622	8599	8623
Viscosity 40 °C	cSt	6.55	26.4	32	44.6	50.5
Viscosity 100 °C	cSt	2.5	5.2	6.1	7.5	8.1
Viscosity Index		272	131	134	134	132
Pour Point	°C	-54	-51	-45	-45	-45
Flash Point C.O.C	°C	119	185	191	229	200